Part No. **ALL19168-19289**

Oversized Oval Head Fasteners

			Silver		Black	
Body Size	Length	Material	10 Pack	50 Pack	10 Pack	50 Pack
7/16"	.500"	Aluminum	ALL19287	ALL19289	ALL19168	ALL19169
7/16"	.500"	Steel	ALL19221	ALL19223	ALL19170	ALL19171

Quick Turn Fastener Measurement Guidelines

To find [A] Fastener Length, add together [B] Spring Reach and [C] Material Thickness [including bracket if applicable]. A=B+C

Quick Turn Fastener Selection

- Determine the total thickness of the panels being joined including mounting brackets and the space between the panels, if any.
- Select the proper body length and spring height combination which provides the proper thickness range.

Spring Length "B"		Fastener Length "A"				
		.400"	.450"	.500"	.550"	.600"
	1" Springs	Total Material Thickness "C"				
	.250"	.165"-.200"	.215"-.250"	.265"-.300"	.315-.350"	.365"-.400"
	.325"	.098"-.133"	.148"-.183"	.198"-.233"	.248"-.283"	.348"-.383"
	1-3/8" Springs					
	.325"	.105"-.148"	.155"-.198"	.205"-.248"	.255"-.298"	.355"-.398"
	.375"	.055"-.098"	.105"-.148"	.155"-.198"	.205"-.248"	.305"-.348"
	.425"	.005"-.048"	.055"-.098"	.105"-.148"	.155"-.198"	.255"-.298"



REV120621

Allstar Performance 8300 Lane Dr., Watervliet, MI 49098
Phone: (269) 463-8000 Fax: (800) 772-2618 www.allstarperformance.com