

# **Quick Turn Fastener Tools**

The quick turn fastener tools fit slot head fasteners and reduces the risk of body panel or fastener damage when using screwdrivers for loosening or tightening.

### Part No. Description

ALL19400.....Tool with Flat Handle

ALL19401.....Tool with Screwdriver Handle




#### **Quick Turn Fastener Measurement Guidelines**

To find [A] Fastener Length, add together [B] Spring Reach and [C] Material Thickness [including bracket if applicable]. A=B+C

#### **Quick Turn Fastener Selection**

- Determine the total thickness of the panels being joined including mounting brackets and the space between the panels, if any.
- Select the proper body length and spring height combination which provides the proper thickness range.

		Fastener Length "A"				
		.400"	.450"	.500"	.550"	.600"
	1" Springs	Total Material Thickness "C"				
	.250"	.165"200"	.215"250"	.265"300"	.315350"	.365"400"
	.325"	.098"133"	.148"183"	.198"233"	.248"283"	.348"383"
	1-3/8" Springs					
	.325"	.105"148"	.155"198"	.205"248"	.255"298"	.355"398"
	.375"	.055"098"	.105"148"	.155"198"	.205"248"	.305"348"
	.425"	.005"048"	.055"098"	.105"148"	.155"198"	.255"298"



REV101923

## Allstar Performance 8300 Lane Dr., Watervliet, MI 49098 Phone: (269) 463-8000 Fax: (800) 772-2618 www.allstarperformance.com