



Part No. ALL56405-56525

Aluminum Suspension Tubes

Clear anodized tubes have a machined wrench flat on one end for ease of adjustment. Tubes have .156" wall thickness, are available in two diameters and a variety of lengths. The 56400 series tubes are 7/8" in diameter and both ends are tapped 5/8", one RH and LH. The 56500 series tubes are 1" in diameter and both ends are tapped 3/4", one RH and one LH. 6061-T6 aluminum.



Length	5/8" Thread 56400 Series	3/4" Thread 56500 Series
5"	ALL56405	-
6"	ALL56406	-
7"	ALL56407	-
8"	ALL56408	-
9"	ALL56409	-
10"	ALL56410	-
11"	ALL56411	-
12"	ALL56412	ALL56512
13"	ALL56413	ALL56513
14"	ALL56414	ALL56514
15"	ALL56415	ALL56515
16"	ALL56416	ALL56516
17"	ALL56417	ALL56517
18"	ALL56418	ALL56518
19"	-	ALL56519
20"	-	ALL56520
21"	-	ALL56521
22"	-	ALL56522
23"	-	ALL56523
24"	-	ALL56524
25"	-	ALL56525
26"	-	-
27"	-	-
28"	-	-
29"	-	-
30"	-	-

REV042022

Allstar Performance 8300 Lane Dr., Watervliet, MI 49098
Phone: (269) 463-8000 Fax: (800) 772-2618 www.allstarperformance.com