

## **Spring Pre-Loader**

Pre-loader allows use of a softer spring rate that is "pre-loaded" at ride height. The pre-loaded spring will have less rate increase as the suspension travels. For example, a 150 lb./in. spring can be pre-loaded to 400 lbs. at ride height, but still only increases at a rate of 150 lb./in. as suspension travels. The entire unit may also be exchanged with another unit with a different rate spring pre-installed to allow spring rate changes without affecting ride height. Commonly used on the rear coil-overs, pre-loader requires 3" l.D. spring, includes a thrust bearing set and fits most shocks. Note: Unit is typically installed with slotted inner half towards the shock body. Always check components for possible interference.

| Part No. | Description                     |
|----------|---------------------------------|
| ALL64230 | .Pre-Loader For 10" Tall Spring |
| ALL64232 | .Pre-Loader For 12" Tall Spring |
| ALL64234 | .Pre-Loader For 14" Tall Spring |

| Part No. | <b>Replacement Parts</b> |
|----------|--------------------------|
| ALL64212 | .3" Thrust Bearing Set   |
| ALL99325 | Inner Teflon Ring.       |
| ALL99326 | .Outer Teflon Ring       |





**Related Parts** 

ALL11187.....Pre-Loader Body Wrench ALL11188.....Pre-Loader Nut Wrench

> Allstar Performance 8300 Lane Dr., Watervliet, MI 49098 Phone: (269) 463-8000 Fax: (800) 772-2618 www.allstarperformance.com