



Scale Buddy

SETUP INSTRUCTIONS

Scale Buddy is designed to replicate the weight of the driver when scaling a car using a water filled bladder(s).

Contents List:

- A. Scale Buddy
- B. Fill Adapter
- C. Drain Adapter with Valve

Filling Instructions:

1. Remove upper and lower protective sealing caps.
2. Install the included fill and drain fittings into the Scale Buddy.
3. Verify the drain valve is in the closed position.
4. Place empty Scale Buddy in driver's seat with drain valve at the bottom and facing out.
Note: Facing the drain out will allow you to connect a garden hose to the valve and drain your Scale Buddy for easy removal when finished scaling your car.
6. Fill Scale Buddy slowly until weight reaches approximately 100 lbs. or less to match the weight of the driver.
Note: It may be necessary to stop filling unit and loosen the top fitting to release any trapped air.
7. Once the Scale Buddy has been filled to the correct amount remove the fill valve and return the protective cap.

Draining Instructions:


1. Connect a standard garden hose to the lower drain adapter.
2. Pass the hose through an opening in the interior lower than the drain valve.
3. Turn the valve to the open position.
4. Loosen the upper protective sealing cap to allow air to vent.
5. Remove Scale Buddy from car.




Fill Adapter



Drain Adapter w/ Valve



Closed Position



Open Position

Allstar Performance 8300 Lane Dr., Watervliet, MI 49098
Phone: (269) 463-8000 Fax: (800) 772-2618 www.allstarperformance.com